

CAT. NO. C13
(REPRESENTS CAT. NO. C17)

FIG. 1

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. C17 is similar to Cat. No. C13 except it is a 2-wire connector. Refer to Ill. 1 for further details.

1. Cord Entry - Overall dimensions 9/16 in (14.2 mm) tapering to 15/32 in (11.9 mm) by 9/16 in (14.2 mm) tapering to 15/32 in (11.9 mm) by 3/4 in (19.0 mm) long for Cat. Nos. C13 and C17.

* **2. Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.**

| Cord Size (AWG) | Cord Type | USL | CNL or CSA Certified |
|--------------------|---------------------------------------|-----|----------------------------|
| 18 | SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO | YES | YES |
| | SVT, SVTO, SVTOO | YES | YES |
| 17 | SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO | YES | YES |
| | SVT, SVTO, SVTOO | YES | YES |

3. Contacts - Nonpolarized, Cat. No. 1307, see Vol. 1C, Sec. 7. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 29/32 in (23.0 mm) by 5/8 in (15.8 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 2-17/32 in (64.2 mm) including cord entry.
6. Premold Insert - Molded of Recognized Component plastic (QMFZ2) Noryl SE1GFN1, flame class 94HB, manufactured by Sabic Innovative Plastics. Overall dimensions 23/32 in (18.2 mm) wide, 1-3/16 in (30.1 mm) long, 7/16 in (11.1 mm) high.
7. Marking - (Not shown). Listee's name or trademark molded on body.