



Ref. Certif. No.

SE-108564M1

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Screwdriver and impact wrench

Name and address of the applicant

Ets Georges Renault
38 rue Bobby Sands, 44818 St Herblain,
France

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Same as applicant

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

36VDC

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

EAB***_**-**_*

Additional information (if necessary may also be reported on page 2)

☒ Additional Information on page 2-3

A sample of the product was tested and found to be in conformity with

IEC 62841-1:2014
IEC 62841-2-2:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

2209269STO-001, 2209269STO-002

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden

Date: 01 December, 2022

intertek

Signature:

Henrik Wikström

Additional information

The nutrunner can be powered by 36V battery.

The tool is compatible with the separately sold accessories:

- Tracker – refers to the Tracker accessory module, is designed to measure a distance between the tool and the tracking base system, using UltraWide Band (UWB) waves. Tracker has no impact on the safety aspects of the tool.
- BCR - Bar Code Reader
- Crowfoot – An extension to reach in inconvenient spaces
- eLINK – Refers to the eLINK accessory module, which is designed to allow connection of additional devices such as Tracker. It also provides lighting of the work area.

Type key: EAB***-**-**

First asterisk	Can be "A", "C" or omitted a. omitted = firmware with single Pset (B-FLEX) b. A = firmware with multiple Pset (B-FLEX advanced) c. C = WiFi communicating tool (EABcom)
Second asterisk	Can be "H" or omitted a. omitted = 90° angle gear box b. H = 110° angle gear box
Third asterisk	Rated max. torque value in Nm, a. value in following range: 15, 26, 29, 32, 45, 50, 60, 75, 90, 95
Fourth asterisk	Rated max. speed in Rpm, a. value in following range: 240, 300, 330, 370, 410, 450, 500, 560, 900
Fifth asterisk	Output shaft type a. omitted = can be Square drive 1/4", 3/8" or 1/2" b. 4S = Square drive 1/4" c. 10S = Square drive 3/8" d. 4Q = Hexa. Female 1/4" e. SQ1/2 = Square drive 1/2" f. HAD = Hold and drive
Sixth asterisk	Additional accessory a. omitted = no accessory b. eLINK = eLINK module installed c. BCR = Barcode reader installed d. QRX = RFID reader installed
Seventh asterisk	Specific attachment for GFA accessory a. Omitted = no attachment b. DU = compatible with GFA type "closed crowfoot" c. DUO = compatible with GFA type "open crowfoot", secondary trigger mounted

Date: 01 December, 2022

Signature:





Ref. Certif. No.

SE-108564M1

This product, with or without the Tracker, BCR, crowfoot accessories, complies with:
EN 62841-1:2015+AC:2015 and EN 62841-2-2:2014+AC:2015
BS EN 62841-1:2015 and BS EN 62841-2-2:2014
CSA C22.2 No. 62841-1:15 (R2020) and CSA C22.2 No. 62841-2-2:16
UL 62841-1:2015 and UL 62841-2-2:2016

This certificate replaces CB certificate SE-108564, dated 08 July 2022. A new certificate has been issued due to a component replacement in the critical components list.

Date: 01 December, 2022

Signature:

A handwritten signature in black ink, appearing to be 'H. H. H.', is written over the signature line.