

SE-117800

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE	
Product	Battery driven nutrunner
Name and address of the applicant	Ets Georges Renault, 38 rue Bobby Sands 44818 St Herblain FRANCE
Name and address of the manufacturer	Same as applicant
Name and address of the factory Note: When more than one factory, please report on page 2	Same as applicant Additional Information on page 2
Ratings and principal characteristics	18VDC, 36VDC
Trademark / Brand (if any)	Desoutter
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	E*BS**-*-*
Additional information (if necessary may also be reported on page 2)	
A sample of the product was tested and found to be in conformity with	IEC 62841-1:2014 IEC 62841-2-2:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	2508504STO-001, 2508504STO-002
This CB Test Certificate is issued by the National Certification Body	

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB Torshamnsgatan 43 Box 1103 SE-164 22 Kista, Sweden

Date: 21 October, 2025

intertek

Signature:

Anneli Averland Johansson

1/2 EMG



SE-117800

Additional information

Type designation key:

E*BS**-*-*-*

First asterisk Second asterisk Third asterisk

A or I, $A = 90^{\circ}$ angle gear box, I = Inline tool = no angle gear box.H or omitted, H = 110° angle gear box, omitted = 90° angle gear box.

Rated max. torque value in Nm.

Value in following range: 7, 8, 10, 12, 14, 15, 17, 24, 27

Forth asterisk

Rated max. speed in Rpm.

Value in following range: 460, 500, 800, 950, 1100, 1300, 1500, 1700

Fifth asterisk

Output shaft type. Omitted = can be Square drive 1/4", 3/8" or 1/2"

4S = Square drive 1/4" (cylindrical retainer) 4SB = Square drive 1/4" (spheric retainer=Ball retainer)

10S = Square drive 3/8" (cylindrical retainer)

4Q = Hexa. Female 1/4"

Sixth asterisk

Specific attachment for GFA accessory.

Omitted = no attachment

DU = compatible with GFA type "closed crowfoot"

DUO = compatible with GFA type "open crowfoot", secondary trigger mounted

Seventh asterisk

Workshop compatibility

Omitted = no specific requirement ESD = compliant with ESD/EPA area

This product complies with:

EN 62841-1:2015 + AC.2015 + A11:2022

EN 62841-2-2:2014 + AC:2015 BS EN 62841-1:2015+A11:2022 BS EN 62841-2-2:2014

CAN/CSA C22.2 No. 62841-1:15 CAN/CSA C22.2 No. 62841-2-2:16

UL 62841-1:2015 UL 62841-2-2:2016

Date: 21 October, 2025

Signature:

2/2

EMG