

Fuji USER MANUAL

DRILLS

MODELS : FRD-6S-2, -3



FRD-6S-2, -3

SPECIFICATIONS

Model	Drilling Capacity (Guidance)		Stall Torque			Free Speed	Spindle Thread Size	Chuck Capacity	Side to Center		Overall Length		Mass		Max.Air Consumption		Air Inlet ThreadSize	Air Hose Size	
	mm	in	N·m	kgf·m	ft·lb	min ⁻¹	in	mm	mm	in	mm	in	kg	lb	Nm³/min	Nft³/min	in	mm	in
FRD-6S-2	6	1/4	2.5	0.25	1.8	4300	U3/8-24	6.5	21	⁵³ / ₆₄	206	⁸⁷ / ₆₄	0.9	2	0.43	15.2	PT or NPT1/4	9.5	³ / ₈
FRD-6S-3	8	⁵ / ₁₆	2.9	0.3	2.1	2800	U3/8-24	8	21	⁵³ / ₆₄	208	⁸³ / ₁₆	1	2.2	0.43	15.2	PT or NPT1/4	9.5	³ / ₈

The performance figures are at 0.63MPa (6.3bar).

⚠ Refer to "The Instructions and Warning for Safety Use" enclosed in each tool box.

Fuji Industrial Technique Co.,Ltd.

2-1-14, Kamiji, Higashinari-ku, Osaka, 537-0003 Japan

Tel : 81-6-6972-2335

Fax : 81-6-6972-2380

