

Fuji USER MANUAL



www.fujitools.com

OIL PULSE WRENCHES

MODELS : FL-4-3, -4D-3, -30

FL-4-3 P



FL-4-3 BF



FL-4-3 BF EC



FL-4-3



FL-4D-3, -30

FL-4D-3



FL-4D-3 EC



FL-4D-30



〈BIT SIZE〉

	FL-4D-3	FL-4D-30
	A : 9.5mm	A : 13mm
	B : 12mm	B : 16mm

SPECIFICATIONS

「Scan code to download this document and see this tool on our online catalogue」

Model	Bolt Size	Recommended Torque Range (0.5~0.63MPa)	Rotational Frequency	Square Drive Size	Bit Shank Size	Air Consumption (At Load)	Mass (without socket)	Overall Length (without socket)	Air Inlet Thread Size	Air Hose Size
	mm	N·m	min ⁻¹	mm	mm	m ³ /min	kg	mm		mm
FL-4-3	M6	16~24	6,700	9.5	—	0.36	0.79	140	Rc 1/4	6.3
FL-4D-3	M6	14~20	6,700	—	6.35	0.36	0.79	140	Rc 1/4	6.3
FL-4D-30	M6	14~20	6,700	—	6.35	0.36	0.79	140	Rc 1/4	6.3

The performance figures are at 0.63MPa (6.3bar).

Refer to "The Instructions and Warning for Safety Use" enclosed in each tool box.

Fuji Industrial Technique Co.,Ltd.

2-1-14, Kamiji, Higashinari-ku, Osaka, 537-0003 Japan

Tel : 81-6-6972-2335

Fax : 81-6-6972-2380

ASSEMBLY TOOLS

ABRASIVE TOOLS

DRILLS / TAPPERS

PERCUSSIVE TOOLS

AIR MOTORS

OTHER PRODUCTS

